## Health IT Standards Committee

A Public Advisory Body on Health Information Technology to the National Coordinator for Health IT



## **NwHIN Power Team**

Final Recommendations for RESTful Exchange Standards

August 22, 2013

## **NwHIN Power Team Membership**



- Dixie Baker, Chair (Martin-Blanck and Associates)
- David McCallie, Co-Chair (Cerner)
- Jitin Asnaani (AthenaHealth)
- Keith Boone (GE Healthcare)
- Kevin Brady (NIST)
- Keith Figlioli (Premier)
- Ollie Gray (DOD)
- Josh Mandel (Harvard Medical School)
- Wes Rishel (Gartner)
- Cris Ross (Mayo)
- Arien Malec (Relay Health)
- ★ ONC support: Avinash Shanbhag, Jamie Parker, and Debbie Bucci

## Agenda



- Review and update of assigned task
- Review of preliminary recommendations presented to HITSC in June
- Results of coordination with Privacy and Security Workgroup and Consumer Technology Workgroup
- Final recommendations

Acronyms defined on slide 22

## **Initial Task Assignment**



- Recommend whether ONC should consider enhancing the current portfolio of transport standards to support consumer exchanges for Stage 3 meaningful-use (and beyond)
  - Consider Blue Button Plus (BB+), HL7 Fast Healthcare Interoperability Resources (FHIR), and RESTful Health Exchange (RHEx) to identify industry trends and emerging standards
  - NwHIN Power Team lead, with inputs from Privacy and Security Workgroup and Consumer Technology Workgroup

## **Task Update**



- Preliminary recommendations presented to HITSC at June meeting
  - Expanded scope of applicability beyond consumer-provider exchanges to include any health information exchange that can be supported using a RESTful service

## **Initiatives Reviewed (1 of 2)**



#### Blue Button Plus (BB+)

- Standards and Interoperability (S&I) Framework Initiative formerly known as Automated Blue Button (ABBI) for exchanges between providers and consumers or consumer-named third parties
- BB+ "Push" uses the Direct Protocol
- BB+ "Pull" specifies a RESTful exchange that uses OAuth2 to authorize an application to query and pull data from an EHR, and FHIR for query and retrieval of selected EHR resources
- BB+ "Pull" includes a Registry Service that distinguishes two categories:
  - "Trusted registration" app is registered with the Service based on its ability to protect the OAuth2 token and the client secret returned by the data provider
  - "Open registration" app is not registered with the Registry Service

## **Initiatives Reviewed (2 of 2)**



- HL7 Fast Healthcare Interoperability Resources (FHIR) specification
  - Healthcare content standard used to support BB+ "Pull" query and retrieval
- RESTful Health Exchange (RHEx) Project
  - Federal Health Architecture + S&I Framework sponsored initiative developing working prototypes demonstrating the use of RESTful services to support health information exchanges
  - Uses OAuth2 for application authorization, OpenID Connect for sharing identity attributes, and hData for content (may migrate to FHIR)

## **Two Levels of Specifications Emerged**



## Lower Level Building Blocks

- HTTPS secure web-based transport
- OAuth2 authorization of third-party applications
- OpenID Connect sharing of identities and attributes
- FHIR simplified, structured content for RESTful exchange

## Higher Level Applications

- BB+"Pull" consumer or authorized third-party query and retrieval of health data
- RHEx demonstration prototypes of RESTful health exchanges

Building blocks are used to build use-case-specific applications

#### OAuth2



- IETF Standard for remote service & third-party authorization (RFC 6749)
- Flexible framework that supports numerous options, and thus needs to be profiled for specific use cases (e.g., healthcare provider-consumer exchanges)
- Closely tied to HTTP, and thus assumes browser useragents
- Used by both RHEx and BB+ Pull
- Status: Balloted standard widely used by major Internet companies (Google, Facebook, eBay, etc.)

### **OpenID Connect**




- OpenID Foundation (OIDF) Pre-standard for remote authentication
- Communicates authenticated user information from one service to another, such as for single sign-on
- Similar to how traditional SOAP web services pass security assertions using SAML
- Designed to replace "OpenID 2.0", which has seen significant uptake among major Internet companies
- Layered on top of OAuth2, and thus can be co-deployed
- Status: Emerging standard in limited, but growing, use for passing user authentication assertions; used by RHEx Project

#### **FHIR**




- New HL7 standard in development strong support by HL7 leadership & rapidly emerging industry interest
- Focuses on "resources" used for exchange; each resource includes:
  - Defined, simple, structured data (may be mapped to RIM, but need not be computable)
  - Extensions (formally defined & published)
  - Narrative
- Emphasis on simplicity, implementability, and human readability
  - Single syntax for documents, messages, queries, services, etc.
  - Specification includes RESTful transport, but other transports may be used
- Licensed free of charge
- Status: Base specification published as DSTU on August 13, 2013, now defining resources; used by BB+ for query and retrieval

## BB+ "Pull" Example



### **Initial Readiness Assessment**





**Adoptability** 

Red Type = building blocks
White box = projects reviewed

## **Initial Overarching Conclusion**



Secured RESTful transport (HTTPS)

+

**OpenID Connect** authentication

+

**OAuth2** authorization

+

**FHIR** healthcare content



a safe and appropriate set of standards to use as building blocks for more complicated healthcare applications

## Since we last talked about this subject...



 NwHIN Power Team has presented these concepts, and its conclusions and recommendations to the Privacy and Security Workgroup and the Consumer Technology Workgroup

## Privacy and Security Workgroup Recommendation: IHE Internet User Authorization (IUA) Profile A Public Advisory Body on Health IT Standards Committee A Public Advisory Body on Health Information Technology

- Leverages NwHIN-recommended standards to address use cases in which a resource service needs to make additional access-control decisions beyond those made by the OAuth2 system
  - e.g., data segmentation for privacy, emergency breakthe-glass override, role-based enforcement, purposeof-use decisions
  - Uses JSON Web Tokens (JWT) and optionally SAML tokens, with well-defined user-context attributes
- Status: Draft for Public Comment published in June 2013

# Consumer Technology Workgroup Observation: OAuth2 Dependency on Portal Identity Management A Public Advisory Body on Health IT Standards Committee A Public Advisory Body on Health IT on the National Coordinator for Health IT

- BB+ "Pull" redirects patient authentication to provider's portal authentication service – so OAuth2 authorization of a requesting app depends upon the strength of the portal's identity management policies and technology
  - Providers need to make sure that the level of assurance provided by their portal identity management approach is sufficiently robust



# Final, Coordinated Conclusions and Recommendations

## Coordinated Conclusions and Recommendations (1 of 2)



Health IT Standards Committee
A Public Advisory Body on Health Information Technolog
to the National Coordinator for Health IT

- Secured RESTful transport (HTTPS), OpenID Connect, OAuth2, and FHIR can be used together to build safe healthcare applications: we recommend ONC support the development and piloting of these standards as candidate building blocks for healthcare applications
  - BB+ "Pull" holds potential as a national implementation specification for future meaningful-use Editions, but further development and piloting are needed
  - RHEx Project is a useful demonstration of how these standards can be used together to support robust, but simple healthcare exchange

## Coordinated Conclusions and Recommendations (2 of 2)




Health IT Standards Committee
A Public Advisory Body on Health Information Technolog
to the National Coordinator for Health IT

- IHE IUA profile appropriately constrains and structures OAuth2
  tokens to support sharing of user-context assertions such as
  "purpose of use" and is recommended for use in environments
  that require coexistence with existing profiles based on IHE
  constrained user-context assertions
- BB+ concept of implementing a Registry Service to recognize two types of registration "trusted" and "open" assumes policy that has not been established and implies a level of app "trustworthiness" that may not be justified: we recommend ONC ask the Privacy and Security Tiger Team to address the questions of 1) whether "trusted registration" with a Registry Service should be required for BB+ "Pull" applications, and 2) if so, what should "trusted" entail

## **FINAL Readiness Assessment**





**Adoptability** 

Red Type = building blocks
White box = projects reviewed

### **FINAL Overarching Conclusion**



Secured RESTful transport (HTTPS)

+

**OpenID Connect** authentication

+

OAuth2 authorization and, as applicable, the IHE Internet User Authorization (IUA) Profile

+

FHIR healthcare content



a reasonable and appropriate set of standards to use as building blocks for more complicated healthcare applications

## **Acronyms**



Acronym	Expansion	Acronym	Expansion
ABBI	Automated Blue Button	JWT	Javascript Object Notation (JSON) Web Token
BB+	Blue Button Plus (formerly called Automated Blue Button or ABBI)	NwHIN	Nationwide Health Information Network
DSTU	Draft Standard for Trial Use	OIDF	OpenID Foundation
EHR	Electronic Health Record	REST	REpresentation State Transfer
FHIR	Fast Healthcare Interoperability Resources	RFC	Request for Comment
IHE	Integrating the Healthcare Enterprise	RHEx	RESTful Health Exchange
HL7	Health Level Seven	RIM	Reference Information Model
HTTPS	Hypertext Transfer Protocol Secure	SAML	Security Assertions Markup Language
IETF	Internet Engineering Task Force	S&I	Standards and Interoperability
IUA	Internet User Authorization	SOAP	Simple Object Access Protocol

